



Specifications

- Cold Water Working Pressure: 2500 kPa (25 BAR)
- Gas Working Pressure: 2100 kPa (21 BAR)
- Max Working Temperature: 95 degrees C
- Thread: BSP to ISO 228
- DZR Brass Nickel plated
- Watermarked (WMTS012)

Features

- Suitable for potable / drinking Water and gas applications
- Flow will occur when the lever is in line with the body of the valve
- Blow proof spindle

Dimensions (mm)

Size	L1	L2	H1	H2	W	TH
15mm (1/2")	58	101	48	44	30	1/2"
20mm (3/4")	66	101	48	48	37	3/4"
25mm (1")	81	101	55	52	46	1"
32mm (1 1/4")	91	140	80	71	58	1 1/4"
40mm (1 1/2")	102	140	92	77	69	1 1/2"
50mm (2")	121	140	108	85	84	2"

Materials

#	PART	MATERIAL
1	Body	DR Brass
2	Seal	PTFE
3	Ball	DR Brass
4	Spindle	DR Brass
5	O Ring	FKM
6	Handle	Stainless Steel
7	Lock Nut	Stainless Steel
8	Bonnet	DR Brass

Warranty

24 months

For Further Information

📧 info@valvewarehouseaustralia.com.au

☎ 03 9421 0042

Valve Warehouse ABN 33 632 515 149